

MADISON COUNTY HIGHWAYS 3.30

NO. <u>31</u>	SECTION (S)	NAME <u>A. W. Wilson</u>
FROM <u>Junction C-5 - Laf. - Pl. City</u> TO <u>Junction U.S. #42</u>		
LENGTH <u>17424</u> (IN FEET) MILES <u>3.30</u>		
PAVEMENT TYPE <u>Bit Surf. Treated</u> WIDTH <u>16'</u>		
WIDTH OF R OF W <u>50</u> WIDTH OF BERMS <u>4'</u>		
FEET <u>17424</u> FEET FEET		
TWP. <u>Canaan</u> MILES <u>3.30</u> TWP. MILES TWP. MILES		
REMARKS <u>COUNTY ROAD</u>		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	<u>RR#1</u>		<u>35</u>	<u>Laid out 1833 See Alders Mt.</u>
	<u>Rd Imp. R#2</u>		<u>220</u>	<u>Imp. 1892 " A.W. Wilson Rd. Imp.</u>

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
<u>1953</u>	<u>D-46 Stone</u>	<u>County</u>	<u>Road base built up to 8"</u>
<u>1954</u>	<u>Tar & 46 Stone</u>	<u>"</u>	<u>Surface treated</u>

31 IMPROVEMENTS Cont. 330

YEAR	TYPE OF	APPLIED BY	REMARKS
1956	Tar & #46 stone	County	Road surface treated with tar & #46 stone.
1958	ME3 #6 stone	"	Spottsealed.
1959	RT#6 stone	"	Surface treated
1961	RT#9 & stone	"	" "
1964	TAR & #6 STONE	"	" "
1967	TAR & #6 STONE	COUNTY	SURFACE TREATED
1970	TAR & #6 STONE	COUNTY	SURFACE TREATED
1973	RS25 #8 stone	County	Surface treated
1976	RS2 #8	County	Surface treated 12,268 gal. RS2, 433,85 ton #8
1979	13,750 gal. RS-2	Hensley	surface treated
1982	500.10 tons #8 12,375 Gal RS-2	Buckeye County	Surface treated
1985	RS2 #8 STONE	KOCK & NORTHWOOD	11,730 GAL RS2 - 433,90 TON #8 - OLENS
1999	Spot Patch & Seal	County	1062 Ton #04 from Northwood
1999	Armor Plate	County	21,265 Gal CRS2P 639 Ton #57 from Oden
11	Chip & Seal		21,265 " " 468 Ton # 8 ^s National
11	Triple Seal		15,103 " " 476 Ton # 8 ^s National