

MADISON COUNTY HIGHWAYS

6.19

NO. 110	SECTION (S)	NAME Lafayette - Mechanicsburg Rd. - ARBUCKLE
FROM	junction US#40	TO junction SR#187
LENGTH	32683 (IN FEET)	MILES 6.19
PAVEMENT TYPE	Bit. Surf. treated	WIDTH 16
WIDTH OF R OF W	40'	WIDTH OF BERMS 3
TWP. Deer Creek	MILES 2.62	TWP. Somersford MILES 3.57
REMARKS	COUNTY ROAD	

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
				Section Lafay - SR#38 Blacktopped prior to 1950

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1953	Blacktopped	County Combined	Primed & Sealed from SR#38 to Junct. Gwynne Rd
"	"	"	Junction Gwynne Rd to SR#187

IMPROVEMENTS Cont. 110 6.19

YEAR	TYPE OF	APPLIED BY	REMARKS
1955	Tare #5 Stone	County	Surface treated from SR #38 to Brynne Rd. Spot sealed. (March) Sealed
1958	MC34 6 stone	" Combined	
1958	Tare #6 Stone	"	
1961	" "	"	"
1964	" "	"	"
1967	RS2 #6 Stone	COUNTY	SURFACE TREATED
1970	RS21 #8 Stone	County	Surface treated
1971		County	Cut Barm - S.R. 38 to S.R. 187
1973	RS25 #5 Stone	County	Oil Surface treated
1976	RS2 + #8	County	18,563 GAL. RS2, 837.10 ton #8
1979	22,150 gal. RS2	Hensley	surface treated
1984	918.05 TON #8 19,610 GAL. RS-2	Koch-W.K.W.	surface treated
1987	518.00 TONS #8 20,782 GAL. RS2	COUNTY & CENTRAL OIL	SURFACE TREATED
1997	404 asphalt	County	Pave 1,933 Tons
1997	CR52P #8 Stone	County	Chip Seal 27,161 Gals 890 Tons