

Amish

MADISON COUNTY HIGHWAYS

3.16

NO. 30	SECTION(S) H	NAME Converse-Huff. - CHANGE TO AMISH ROAD
FROM Junction C-5 Laf.-Pl. City TO Junction C-24 Rosedale-Pl. City		
LENGTH 16516 16685 (IN FEET) MILES 3.16		
PAVEMENT TYPE Bit. Surf. Treated WIDTH 16		
WIDTH OF R OF W 50' WIDTH OF BERMS 4'		
FEET 71880 12091 FEET 4636 4594		
TWP. Caanan MILES 2.29 TWP. Darby MILES .87 TWP. MILES		
REMARKS COUNTY ROAD		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	RR #1		21	Laid out 1821 - see Ruppell's Rd
	R #1		255-262	Impr. 1882

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1953	Tar & 6 stone	Count. /	Surface treated.
1956	Asph & 6 stone		

30 316

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1957	Tar & Stone	County	Surface treated (Jct 5 to Jct #4) 5
1960	TAR & #6 STONE	COUNTY	SEALED SURFACE FROM JCT C-5 LAFAYETTE-PLAIN
1963	" "	"	CITY RD. TO JCT C-5
1963	" "	"	Surface treated from C-5 to C-5
1966	Tar & #6 Stone	County	Surface treated from #5 to #5
1969	Tar & #6 Stone	County	Surface treated from #5 to #5
1971		County	Cut BURM from #5 to #5
1972	RS-2 & #8 Limestone	County	Surface treated from #5 to #5
1975	12,861 GAL RS2	VAN CANT & COUNTY	SURFACE TREATED - #5 TO #5 - 395.00 ^{TONS} #8 LIMESTONE
1978	13,500 gal. RS.2	Ray Hensley	SURFACE TREATED - #5 to #5 - 428.50 tons #8 limestone
1981	388.00 TON #8 12,404 GAL RS2	W.K.W. & COUNTY	SURFACE TREATED (C.R. 5 TO C.R. 5)
1984	489.3 TON #8 12,832 Gal. RS-2	Koch - W.K.W.	Surface Treated (C.R. 5 TO C.R. 5)
1987	339.00 TON #8 12,726 GAL RS2	COUNTY & CENTRAL OIL	SURFACE TREATED - (C.R. 5 TO C.R. 4)
199	Paved	Hefner Paving	
199	Berm	County Crew	
1997	Crack Seal	County Crew	720 gal 16 Ton #9 limestone
2000	Paved	Northwood / ODOT	(US42-CR7) 1" overlay, 963 Ton #404

MADISON COUNTY HIGHWAYS 3.52

NO. 30	SECTION (S) B.	NAME Converse - Huff
FROM Junction C-24 - Rosedale - Pl. City TO Junction C-7 - East Pike		
LENGTH 14414 18586 (IN FEET) MILES 2.73 3.52		
PAVEMENT TYPE B.t. Surf. Treated WIDTH 16		
WIDTH OF R OF W 50' WIDTH OF BERMS 4'		
TWP. Converse FEET _____ MILES _____ TWP. Darby FEET 14414 MILES 2.73 TWP. _____ FEET _____ MILES _____		
REMARKS COUNTY ROAD 3.52		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
				See Sect. "A"

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1953	Tar & 6 stone	County	Surf. treated from C-5 to Route #48
1954	" "	"	" " Route #48 to C-7.

IMPROVEMENTS Cont. ³⁰ ^{3.52}

YEAR	TYPE OF	APPLIED BY	REMARKS
1957	Asph & #6 stone	County	Surface treated
1958	Tar & #6 stone	"	" " 1/2 (northside) from CR #5 to SR #42
1959	RT9 & #6 stone	"	Surface treated from SR #42 to C-7 (1.35 mile)
1962	Tar & #6 stone	"	Surface treated " " "
1962	RT9 #5 & #6 stone	"	" " from SR 42 to CR #5 (1.38 mile)
1965	TAR & #6 STONE	COUNTY	SURFACE TREATED
1968	Tar & #6 stone	County	Surface treated from CR 5 to CR 7
1971	MC5 & #8 stone	County	Surface treated from C.R. 5 to C.R. 7
1974	361.91 #8 - 333.45 #67 24,939 Gal. RS25	County	Double sealed with #67 & #8 limestone
1977	13,513 Gal. RS2	County - V.C.	Surface treated - 498.50 tons #8 limestone
1980	318.10 tons #8 9,200 Gal. RS2	County W.R.O.	Surface treated (C.R. #5 to C.R. #7)
1983	431.2 tons #8 9,225 Gal. RS2	County	Surface treated (C.R. #5 to C.R. #7)
1986	372.50 TON #8 10,882 GAL. RS2	COUNTY A.M. - W.K.W.	SURFACE TREATED (C.R. #5 TO C.R. #7)
1987	61.00 TON #8 2,200 GAL. RS2	COUNTY & CENTRAL OIL	SURFACE TREATED - (C.R. 24 TO C.R. 5)
1988	2,853.52 lbs #404	County	(C.R. 7 to C.R. 24) 404 ^{Hot mix} Hot mix ^{widen} 20'
2000	CRS2P/#8 stone	county	chip & seal ^{admix} 460 gal 147 ton
2000	CRS2P/#8 stone	county	chip & seal 6314 gal 203 ton