

MADISON COUNTY HIGHWAYS ⁶⁷ 2.40

NO. 67	SECTION (S)	NAME Hicks
Twp Road	FROM Junction SR #323	TO Fayette Co. line
	LENGTH 12565	(IN FEET) MILES 2.40
	PAVEMENT TYPE Gravel	WIDTH 24 75"
	WIDTH OF R OF W 40	WIDTH OF BERMS 3
	TWP Pleasant FEET 12565	FEET _____
	MILES 2.40 TWP. _____	MILES _____ TWP. _____ MILES _____
REMARKS TOWNSHIP ROAD		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	RR #1		111	Laid out 1853

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1956		County	24" cor. pipe laid across road at culvert #1 - 32 in length

IMPROVEMENTS Cont. 67 2.40

YEAR	TYPE OF	APPLIED BY	REMARKS
1958		County	Birms & chos cut from SR 323 to Fayette Co line
1959	Black top	"	Road primed & sealed with "46 stone from SR #323 a distance of 1.9 mile.
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT REPAIRED ^{TREATED}
1960	MC5 #6 STONE	"	SURFACE SEALED FROM SR 323 TO SR 323 ^{H. R. (1.90 mi.)}
1962	Tort #6 stone	"	Road surface sealed a dist. of 1.9 miles
1965	MC5 #6 STONE	"	SURFACE TREATED
1968	Tort #6 stone	County	Surface treated
1971	R.S. #8 stone	County	Surface treated - (O'Ray-Harrison to County line)
1972	RS 24 #8 Stone	County	Surface treated - (O'Ray-Harrison to SR #323)
1974	3,900 Gal. RS #8	County	Surface treated - (C.R. 18 to Co. line) 105.10 ton #8 gravel
1975	4,500 GAL. RS #8	VAN CAMP COUNTY	SURFACE TREATED - 239.15 TONS #8 GRAVEL (SR 323 TO C.R. 18)
1977	3,084 Gal. RS #8	County - v.c.	Surface treated - (C.R. 18 to Fayette Co. line) 110.80 ton #8
1978	3,625 GAL. RS #8	HENSLEY	SURFACE TREATED - (S.R. 323 TO C.R. 18) 278.21 TONS #8 GRAVEL
1982	4,167 Gal. RS #8	Buckeye County	Surface treated (S.R. 323 to C.R. #18) (see card #2)

MADISON COUNTY HIGHWAYS

#2

NO. 67	SECTION (S)	NAME Hicks
FROM Junction S.R. #323 TO Fayette Co. Line		
LENGTH 12565	(IN FEET) MILES 2.40	
PAVEMENT TYPE	WIDTH 15"	
WIDTH OF R OF W 40	WIDTH OF BERMS 3	
TWP Pleasant	FEEET MILES 2.40	FEEET MILES TWP. MILES
REMARKS Township Rd.		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1984	324 TON #8 3400 gal RS-2	Koch-W.K.W.	Surface Treated (C.R. #18 to Co. Line)
1985	RS-2 & #8 STONE	Koch & Northward	S.R. #23 to C.R. #18 - 3,850 GAL, RS-2 - 14402 TON #8 LIMESTONE

