

MADISON COUNTY HIGHWAYS

5.31

NO. 53	SECTION (S)	NAME Kiousville - Georgesville
FROM	Village of Kiousville	TO Franklin Co Line
LENGTH	27826 28037 (IN FEET)	MILES 5.27 5.31
PAVEMENT TYPE	Bit. Surf. treated	WIDTH 16 19.5 (1994)
WIDTH OF R OF W	60'	WIDTH OF BERMS 4
TWP	Fairfield FEET 27826 MILES 5.27	TWP. MILES TWP. MILES
REMARKS	Laidout 1834 See K&G Rd RR#1 pg 47	

COUNTY ROAD HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	Rd Imp R#1		320	Impv 1882 See K&G Rd
	VOLE Comj		583	" 1878 " L&C Rd.

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1951	Tar & 6 stone	County	Surface treated
1954	" "	" "	" "

Kiousville - Dearyville IMPROVEMENTS Cont. 5.31

YEAR	TYPE OF	APPLIED BY	REMARKS
1958	Mc5#6 stone	County	Surface treated.
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1961	Mc5#4 stone	"	Surface treated
1964	Mc L #6 STONE	"	" "
1967	T-35-TYPE A	SOUTHWEST PALEING	T-35 - Kiousville to Franklin on line - 6676 ^{tons}
1975	404 HOT MIX	VAN CAMP	1.5" DEPTH - 16' WIDE - (C.R. 4 TO KIOUSVILLE) 1,771.20 ⁴⁰⁴ TONS
1978	11,400-RS2	Ray Hensley	surface treated 327.05 tons #8 limestone (C.R. 4 TO S.R. 665)
1981	384.00 TONS #8 9,283 GAL RS2	W.K.W. COUNTY	SURFACE TREATED - (S.R. 665 TO C.R. 4)
1984	394.1 TONS #8 9,611 Gals. RS-2	Koch - W.K.W. COUNTY	Surface Treated (S.R. 665 TO C.R. #4)
1987	572.00 TONS #8 18,576 GAL RS2	CENTRAL OIL	SURFACE TREATED (ALL)
1995	CRS2P-#8 Stone	County Road Crew	23,192.14 Gal - 970 Ton Chip Seal/Resurface
1994	asphalt 404	County Road Crew	Ton Trench & widen To 19.5 feet
- 11	4-11 Stone	"	Ton Berin
2000	CRS2P #8 stone	county	chip & seal 2224 gal 613 ton