

MADISON COUNTY HIGHWAYS

4.40

NO. 102	SECTION (S)	NAME Lilly Chapel - Georgesville
FROM	Junction SR 665	TO Franklin Co Line
LENGTH	23021 23232 (IN FEET)	MILES 4.36 4.40
PAVEMENT TYPE	Bit Surf. treated	WIDTH 20
WIDTH OF R OF W	45	WIDTH OF BERMS 3
TWP. Fairfield	FEET 23021 MILES 4.40	FEET _____ MILES _____
REMARKS	COUNTY ROAD	

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	RR #1		72	Laid out 1841 see Georgesville Rd
	VOIC	Comf.	3620425	Impr 1868

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1954	Tars "6 stone	County	Surface treated
1958	"	"	Rd scraped and rebuilt from SR #665 1/4 mile east and entire road spot sealed.

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1958	Tar & #6 stone	County	Surface treated.
1960	R.T. #6 STONE	"	SURFACE SEALED FOR 1.25 MI. FROM SR. #665-
1962	MC 5 #6 stone	"	Surface treated from 665 to Lilly Chapel
1963	Tor #6 stone	"	Surface treated from d. Chap. to Franklin Co Line
1966	MC 5 #6 Stone	County	Surface treated from S.R. 665 to Chapel
1969	R.S. #6 Stone	County	Surface treated
1971	402-T-35	VAN CAMP	5,539.50 TONS - ALL
1985	404 HOT MIX RS#4 FS	COUNTY KOCK NORTHWOOD	CHAPEL TO CO. LINE LEVELED WITH 404 17,717 GAL. RS# - 544100 TON FS
1987	CENTRAL OIL	288.00 TONS #8 10,283 GAL. RS#	SURFACE TREATED (SR. 665 TO LILLY CHAPEL)
1989	519 gal #8 534 gal #9	County	Double surface treat from SR. 665 to County line
1998	Double Chip & Seal	County	37,421 Gal CRS2P, 574 Ton #8, 574 Ton #9

4,140
other side } combined