

MADISON COUNTY HIGHWAYS

NO. <u>18</u>	SECTION (S) <u>A</u>	NAME <u>O'Day-Harrison Rd</u>
FROM <u>SR #56</u>		TO <u>Junction C-9 (Yanketown Pike)</u>
LENGTH <u>31152 30307</u>		(IN FEET) MILES <u>5.9 5.74</u>
PAVEMENT TYPE <u>Bit Surface treated</u>		WIDTH <u>16' - 19' (1996)</u>
WIDTH OF R OF W <u>40</u>		WIDTH OF BERMS <u>3' 2'</u>
TWP <u>Pleasant</u> FEET <u>19536</u> MILES <u>3.70</u>		TWP <u>Range</u> FEET <u>11616</u> MILES <u>2.10</u>
REMARKS <u>COUNTY ROAD</u>		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	<u># 2</u>		<u>pg 137</u>	<u>Imp. 1889 Sec O'Day Rd</u>

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
<u>1951</u>	<u>Tar & 6 stone</u>	<u>County</u>	<u>Surface treated</u>
<u>1954</u>	<u>"</u>	<u>"</u>	<u>"</u>

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1958	RR3 & 6 stone	County	Surface treated
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1961	MC#5 + stone	"	Surface treated
1963	" "	"	" "
1966	MC5 & #6 Stone	County	Surface treated
1967	T-35	COUNTY	PATCHED FROM RR#56 TO COUNTYLINE
1969	tar & #6 Stone	County	Surface treated
1972	RS-2 & #8 Stone	County	Surface treated
1975	23,333 GAL. RS2	VAN CAMP & COUNTY	SURFACE TREATED - 818.20 TONS #8 GRAVEL
1978	24,000 GAL. RS2	HENSLEY COUNTY	SURFACE TREATED - 816.00 TONS #8 LIMESTONE
1987	634,555 TONS #8 21,255 GAL. RS2	CENTRAL OIL	SURFACE TREAT - (ALL)
1990	225,92.15 gal. liquid asphalt 950 tons #8	County	Surface treated entire road sections A+B
1996	404 asphalt	County Road Crew	Trench & Widen 18" W X 4" D
1996	CRS2P / #8 Stone	"	Chip Seal 4' wide on Edges 10,056 Dal / 344 Ton
1996	402 asphalt	Northwood	Pave Leveling C 4,712.69 Tone .75"
1996	404 asphalt	"	Pave Finish C 3,006.14 Ton 1.25"
1996	617 Berm	"	Berm 1,388.22 Ton

MADISON COUNTY HIGHWAYS

NO. 18	SECTION (S) B	NAME O'Day - Harrison Rd
FROM Junction of C-9		TO Fayette Co Line
LENGTH 4177 4277		(IN FEET) MILES 89.81
PAVEMENT TYPE Gravel & #6 stone		WIDTH 16'
WIDTH OF R OF W 40'		WIDTH OF BERMS 3'
TWP Range FEET 4171		MILES 89.81 TWP. _____ FEET _____ MILES _____
REMARKS COUNTY ROAD		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	#2		pg. 137	Imp. 1889 See O'Day Rd

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1956	Bridge	County	New Bridge created 26' wide road widened and rebuilt.

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1957	Blacktopped	County	Road pruned and sealed with "6 lewis" stone.
1958	Asp #6 stone	"	Resurfaced.
1959	Asp #6 stone	"	Surface treated.
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1963	MC5 #6 stone	"	Surface treated
1966	MC5 #6 stone	County	Surface treated
1967	T-35	COUNTY	PATCHED FROM R [#] 56 TO COUNT LINE
1969	Tars #6 stone	County	Surface treated
1972	RS-2 #8 stone	County	Surface treated
1975	23,333 GAL RS2	VAN CAMP COUNTY	SURFACE TREATED - 818.30 TONS #8 GRAVEL
1978	24,000 GAL RS2	HENSLEY	SURFACE TREATED - 816.00 TONS #5 LIMESTONE
1990	22592.15 gal. liquid asphalt 950 tons #8	County	Surface treated the entire road, sections A & B
1996	CRS2 p/ #8 Limestone	County	Chip Seal 4,800 Gal 180 Ton
2000	40% asphalt	Northwood	Phase 2 1,380 Ton