

MADISON COUNTY HIGHWAYS

NO. 24	SECTION (S) A	NAME Rosedale-Plain City
FROM Junction C-28 Weaver Rd		TO Rosedale Junction C-24 & C-124 Vogelsburg Rd
LENGTH 15576		(IN FEET) MILES 2.94
PAVEMENT TYPE Bit & T-32		WIDTH 15'
WIDTH OF R OF W 45		WIDTH OF BERMS 3
TWP. Pike FEET 15576 MILES 2.95		TWP. _____ FEET _____ MILES _____
REMARKS Paved by T-32 to junction with SR #38 - Twp Road.		

Twp Road

2.94

HISTORY

~~0.94~~ - TOWNSHIP - 2.94 - COUNTY ROAD

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	RR #1		38	Laid out 1833 - See Converse Rd
	"		129	Altered 1860 - See Hunt's Plat

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1865			Altered Boyde Bowers Plat. RR #1 pg 156
1953	T. 32	County	Paved by T-32 from Rosedale to SR #38

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1956		County	Floor on Bridge # 24-10 over L. Darby replaced with 2x4 crossed pine covered with 2" layer of T-60.
1957	Asph Stone	County	Road rebuilt from SR #38 to Jct of Gray Ave widened to 16' curbs sealed with #6 lime stone
1960	^{RT 9} TAR & #6 STONE	COUNTY	SURFACE SEALED ENTIRE "A" SECTION all of Road
1963	" "	" "	Surface treated. all
1966	TAR & #6 STONE	COUNTY	Surface treated. all
1969	TAR & #6 STONE	County	Surface treated. All
1973	RS25 #8 stone	County	Surface treated
1976	RS2	COUNTY	9,719 Gal. RS2 - 270.50 ton #8 limestone. 4.0
1980	374.10 tons #8 10,240 Gal. RS2	County W.K.W.	Surface Treated (Pike Lwp) Roadale to C.R. #124)
1984	465.85 TON #8 10,303 gal. RS-2	Koch-W.K.W.	Surface Treated (C.R. #28 TO C.R. #124)
1987	30.00 TONS #8 10,200 GAL RS2	COUNTY + CENTRAL OIL	SURFACE TREATED-
1990	10037.34 gal. liquid asphalt 455 TONS #8	County	Surface treated (C.R. #25 to C.R. #124)
1997	CRS2P #8 Limestone	County	Chip Seal 13,605 Gal 587 Tons

MADISON COUNTY HIGHWAYS

NO. <u>24</u>	SECTION(S) <u>A</u>	NAME <u>Rosedale - Plain City</u>
FROM <u>Rosedale Rd</u>		TO <u>Junction Vogelsburg Rd</u>
LENGTH <u>15576'</u>		(IN FEET) MILES <u>2.94</u>
PAVEMENT TYPE <u>Chip & Seal</u>		WIDTH <u>16'</u>
WIDTH OF R OF W <u>45'</u>		WIDTH OF BERMS <u>3'</u>
TWP. <u>Pike</u>	FEET _____	FEET _____
MILES _____	TWP. _____	MILES _____
REMARKS _____		

Township Road HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
<u>2004</u>	<u>Chip & Seal</u>	<u>County</u>	
<u>2009</u>	<u>Chip Seal</u>	<u>Madison Co Crew</u>	

(SEE OTHER SIDE)

MADISON COUNTY HIGHWAYS

7.63

NO. <u>24</u>	SECTION(S) <u>B</u>	NAME <u>Rosedale - Plain City</u>	<u>C-30 CONVERSE - HUFF</u>
FROM <u>Junction C-124 - Vogelsburg</u>		TO <u>Junction C-5 - Lafayette - Plain City</u>	
LENGTH 28460 <u>24500</u>		(IN FEET) MILES 5.39 <u>4.64</u>	
PAVEMENT TYPE <u>Bit Surf Treated</u>		WIDTH <u>16</u>	
WIDTH OF R OF W <u>45</u>		WIDTH OF BERMS <u>3</u>	
FEET <u>4806</u>		FEET 20654 <u>19694</u>	
TWP. <u>Pike</u> MILES <u>97.96</u>		TWP. <u>Darby</u> MILES 4.48 <u>3.73</u>	
REMARKS <u>Laid out & altered 1833-1860-1865 - See sect A.</u>			

COUNTY ROAD

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	<u>Comf.</u>	<u>Vol. E</u>	<u>330-336</u>	<u>Imp. 1876 - Chockery - Plain City Pike</u>

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
<u>1948</u>	<u>Tar & Gt Stone</u>	<u>County</u>	<u>Surface Treated from Pike Twp line to Jct. C-30</u>
<u>1954</u>	<u>"</u>	<u>"</u>	<u>" " E-125 to " "</u>

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1957		County	Road widened and rebuilt from SR #38 to Jct 138 (Gay, Mo). Sealed & primed and sealed with M&S #6 limestone
1958	Tar #6 stone	County	Surface treated from Jct CR #125 to Jct CR #30
1960	^{R.T. #9} TAR #6 STONE	COUNTY	SURFACE SEALED FROM JCT. C-124 VOGELSBURG RD. TO JCT. C-30 CONVERSE-HUFF RD.
1963	" "	"	Surface treated
1966	Tar #6 Stone	County	Surface treated
1969	Tar #6 Stone	County	Surface treated
1971		County	Cut Berrn
1972	RS-2 #8 limestone	County	Surface treated
1975	15,510 GAL. RS2	VAN CAMP COUNTY	SURFACE TREATED - 466.35 TONS #8 LIMESTONE
1978	16,050 Gal. RS2	Ray Hensley	surface treated - 463.80 tons #8 limestone
1981	507.90 TON #8 14,435 GAL. RS2	WELLS COUNTY	SURFACE TREATED
1984	672.1 Ton #8 12,808 Gal. RS-2	Koch - W.K.W. COUNTY	Surface Treated 1137.95 ton 23311. gal
1987	488.50 TONS #8 17,522 GAL. RS2	CENTRAL OIL	SURFACE TREATED 948.50 ton
1990	Chipseal 4' Edge	clay, County	8838 Dal CRS2P 238 Ton #8 Limestone

MADISON COUNTY HIGHWAYS

NO. 24B	SECTION (S)	NAME Rosedale - Plain City
FROM C-124 (Vogelsburg Rd) TO C-30 (Converse-Huff Rd)		
LENGTH 24,763 (IN FEET) MILES 4.64		
PAVEMENT TYPE Chip & Seal WIDTH 16		
WIDTH OF R OF W 45 WIDTH OF BERMS 3		
TWP. Pike FEET 4806 MILES .96 TWP. Darby FEET 19,694 MILES 3.73		
REMARKS County Rd (also see T-24 A)		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1998	Chip & Seal	County	19,55 Dal CR52P, 602 Ton #0

(SEE OTHER SIDE)