

MADISON COUNTY HIGHWAYS

1/11/18 - 2.23 (County)
- 1.18 (Township)

3.41

3.41 total

| | | |
|------------------------------|---|---------------------------------------|
| NO. 37 | SECTION (S) | NAME Smith-Calhoun |
| Twp. Road. | FROM Franklin Co Line | TO Junction C-34 (Cemetery Rd) |
| | LENGTH 18216 | (IN FEET) MILES 3.41 |
| | PAVEMENT TYPE Crush Stone & Gravel | WIDTH 15 |
| | WIDTH OF R OF W 40' | WIDTH OF BERMS 3 |
| | FEET 11874 | FEET 6342 |
| | TWP. Conaen MILES 2.23 | TWP. Darby MILES 1.18 |
| REMARKS TOWNSHIP ROAD | | |

HISTORY

| PETITIONED | ROAD RECORD BOOK | COMM. VOL. | JOURNAL PAGE | REMARKS |
|------------|------------------|------------|--------------|----------------------------|
| | RR #1 | | 56 | Laid out 1836 see Flint Rd |
| | RR #1 | | 62 | Altered 1837 - Knap Alt |

IMPROVEMENTS

| YEAR | TYPE OF | APPLIED BY | REMARKS |
|------|----------------|------------|---|
| 1956 | Top & 46 stone | County | Road bed built up - 1 new culvert (arch pipe) Road prime & sealed with top & 46 stone from Amity Pike to Franklin Co line |



37 3.41

IMPROVEMENTS Cont.

| YEAR | TYPE OF | APPLIED BY | REMARKS |
|------|---------------------------------|------------------|--|
| 1958 | Pop #6 stone | County | Birms cut. Road bed built up. Road primed and sealed with #6 stone from Amity Pike (CR 36) to Cemetery Rd (CR 34) a total of 1.7 miles |
| 1959 | MC5 #6 stone | " | Surface treated |
| 1962 | Tar #6 stone | " | Surface treated |
| 1965 | Tar & limestone | " | Surface treated |
| 1968 | Tar #6 stone | County | Surface treated |
| 1971 | MC5 #8 stone | County | Surface treated |
| 1973 | RS25 #8 stone | County | Surface treated (Fr Amity Pike to ^{CO. LINE} FRANKLIN) |
| 1974 | 6,003 Gal. RS25 | County | Surface treated - (C.R. 34 to C.R. 36) 163.20 ton #8 limestone |
| 1976 | 5,266 Gal. RS2 | COUNTY | 198.20 ton #8 limestone - (C.R. 36 to Franklin Co. line) |
| 1977 | 7,100 Gal. RS2 | County - V.C. | Surface treated - (C.R. 34 to C.R. 36) 722.50 ton #8 limestone |
| 1978 | 6,600 GAL RS2 | HENSLEY | SURFACE TREATED - (C.R. 36 TO COUNTY LINE) 203.85 TON #8 ^{8 LIMESTONE} |
| 1980 | 1,300 tons #8 1,300 Gal. RS2 | County W.K.W. | Surface treated (Canaan Twp. line to C.R. #36) |
| 1980 | 181.50 ton #8 3,429 Gal. RS2 | County W.K.W. | Surface treated (C.R. 34 to Darby Twp. line) |
| 1981 | 34.40 TON #8 5,963 GAL RS2 | W.K.W. & COUNTY | SURFACE TREATED (C.R. 36 TO FRANKLIN CO. LINE) |

MADISON COUNTY HIGHWAYS

| | | |
|--|-------------|--------------------------------|
| NO. 37 | SECTION (S) | NAME Smith - Calhoun |
| FROM Franklin Co. Line TO Junction C.R. #34 (Cemetery Rd.) | | |
| LENGTH 18216 (IN FEET) MILES 3.41 | | |
| PAVEMENT TYPE Crush Stone & Gravel WIDTH 15 | | |
| WIDTH OF R OF W 40' WIDTH OF BERMS 3 | | |
| TWP Canaan FEET 11874 MILES 2.23 TWP Darby FEET 6342 MILES 1.18 TWP. FEET. MILES | | |
| REMARKS Township Road | | |

HISTORY

| PETITIONED | ROAD RECORD BOOK | COMM. VOL. | JOURNAL PAGE | REMARKS |
|------------|------------------|------------|--------------|-----------------------------------|
| | RR#1 | | 56 | Laid out 1836 see Flint Rd |
| | RR#1 | | 62 | Altered 1837 " Knap Alt |

IMPROVEMENTS

| YEAR | TYPE OF | APPLIED BY | REMARKS |
|-------------|---|---------------|---|
| 1983 | 60.98 ton #3 1,300 Gals. RS-2 | County | Surface Treated (Canaan Twp to C.R. #36) |
| 1983 | 233.70 ton #3 3,675 Gals. RS-2 | County | Surface Treated (Darby Twp to C.R. 34) |



