

MADISON COUNTY HIGHWAYS

0.92

NO. <u>118</u>	SECTION (S)	NAME <u>Ware Rd</u>
Twp Road	FROM <u>Junction SR #29</u>	TO <u>Junction C-27 (Mechb - Sanford)</u>
	LENGTH <u>4858</u>	(IN FEET) MILES <u>.92</u>
	PAVEMENT TYPE <u>Bit Surf. Treated</u>	WIDTH <u>16</u>
	WIDTH OF R OF W <u>40'</u>	WIDTH OF BERMS <u>3</u>
	TWP. <u>Somerset</u> FEET <u>1426</u> MILES <u>.27</u>	TWP. <u>put</u> FEET <u>3432</u> MILES <u>.65</u>
	REMARKS <u>TOWNSHIP ROAD</u>	

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	<u>RR #1</u>		<u>29</u>	<u>Laid out 1828. see Van Ness Rd</u>

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
<u>1955</u>	<u>Black topped</u>	<u>County</u>	<u>Road bed built up - Primed & Sealed with #46 stone</u>
<u>1958</u>	<u>Tar #6 stone</u>	<u>"</u>	<u>Sealed</u>

IMPROVEMENTS Cont.

118

0.92

YEAR	TYPE OF	APPLIED BY	REMARKS
1961	RT9 & stone	County	Surface treated
1963	MC5 & #6 stone	"	"
1966	tar & #6 stone	"	"
1969	RS2 & #6 stone	County	Surface treated
1972	RS2 & #8 stone	County	Surface treated
1975	3,700 GAL RS2	VAN CAMP COUNTY	SURFACE TREATED - 75.00 TONS #8 LIMESTONE
1978	2,000 GAL RS2	HENSLEY	SURFACE TREATED - 39.20 TON #8 GRAVEL
1981	2,950 GAL RS2	WELLS COUNTY	SURFACE TREATED
1984	2,050 gal. RS-2 105.95 TON #8 (TON #8 40. TONS)	Koch - W.K.W.	Surface Treated (C.R. #27 To ^{TWP} G. line) All
1984	2,050 gal. RS-2 105.95 TON #8 (TON #8 40. TONS)	Koch - W.K.W.	Surface Treated (S.R. #29 To Twp. line)
1986	2,173 GAL RS2 57.35 TON #8	AM. F.W.K.W.	SURFACE TREATED - (PIKE TWP)
1986	1,500 GAL RS2 57.35 TON #8	AM. F.W.K.W.	SURFACE TREATED - (SOMERFORD TWP) All
1989	3100 gal RS2 86 tons #8	County	Surface treated Cr. 27 to Sup line
1990	250 gal. liquid asphalt 55 tons #8	County	Surface treated (Somertord Twp)
1997	CRS2P Limestone	County	Chip Seal 3662 Gal 280 Tons
2003	Chip & Seal	County	3104 Gal CRS2P 90 Ton #8 Limestone
2010	Chip & seal	County crew	